

TOPFLEX® 611-C-PUR Motor power supply cable for drag chains

0,6/1kV, EMC preferred type, halogen-free, meter marking



Technical data

- Special-PUR drag chain cable adapted to DIN VDE 0293, 0295, 0250, DIN VDE 0285-525-1 / DIN EN 50525-1
- **Temperature range**
flexing -30°C to +80°C
fixed installation -40°C to +80°C
- **Nominal voltage** U₀/U 600/1000 V
- **Test voltage** 4000 V
- **Coupling resistance**
max. 250 Ohm/km
- **Insulation resistance**
min. 20 MOhm x km
- **Min. bending radius**
flexing 10x cable Ø
fixed installation 5x cable Ø

Cable structure

- Bare copper-conductor, to DIN VDE 0295 cl.6, extra fine-wire, BS 6360 cl.6, IEC 60228 cl.6
- Core insulation PP
- Core identification to DIN VDE 0293 black cores with continuous white numbering
- GN-YE conductor
- Cores stranded together with optimal lay-length and stabilising filler
- Fleece wrapping facilitates sliding
- Inner sheath of TPE
- Tinned copper braided screen, approx. 85% coverage
- Outer sheath of PUR
- Sheath colour grey (RAL 7001)
- with meter marking

Properties

- Adhesion-free, extremely abrasion resistant, halogen-free, resistant to hydrolysis and microbial attack
- resistant to UV-radiation, oxygen and ozone
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

Note

- G = with green-yellow conductor
- For extreme applications extending beyond standard solutions we recommend that you request our questionnaire, which has been especially designed for energy supply systems.
- Please observe applicable installation regulations for use in energy supply chains.
- unscreened analogue type:
TOPFLEX® 611-PUR, confer page 199

Application

As optimized supply cable for the supply to motors, in particular to DNC motors, servo-motors. These cables are specially designed for use in power drag chains, handling equipment, robotics, tooling machinery, processing and manufacturing machinery. Optimised insulation materials ensure resistance to oils (including mineral oils), greases, coolants, hydraulic fluids as well as many alkalis and solvents. Favourable outer diameters, reduced weights and enhanced torsion characteristics assure the use in multi-layer operations with extremely high continuous bending loads. Suitable for outdoor use.

EMC = Electromagnetic compatibility

To optimize the EMC features we recommend a large round contact of the copper braiding on both ends.

CE = The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

Part no.	No. cores x cross-sec. mm²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
22970	4 G 1,5	11,3	99,0	220,0	16
22971	4 G 2,5	13,5	169,0	340,0	14
22972	4 G 4	16,0	234,0	490,0	12
22973	4 G 6	17,8	316,0	680,0	10
22974	4 G 10	22,2	549,0	1035,0	8
22975	4 G 16	27,2	807,0	1460,0	6

Part no.	No. cores x cross-sec. mm²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
22976	4 G 25	31,2	1169,0	1990,0	4
22977	4 G 35	35,2	1680,0	2535,0	2
22982	4 G 50	42,5	2370,0	3360,0	1
22983	4 G 70	48,8	3257,0	4650,0	2/0
22984	4 G 95	54,6	4060,0	6090,0	3/0
22985	4 G 120	58,5	5231,0	7380,0	4/0

Dimensions and specifications may be changed without prior notice. (RD01)



Suitable accessories can be found in Chapter X.

- Cable Gland - HELUTOP® HT-MS-EP4